

Hanza Seal

HANZA SEAL is water-based acrylic primer sealer for interior & exterior use .

General Specifications:

- HANZA SEAL is primer sealer, based on acrylic binder, penetrates surfaces to increase the adhesion of paint coats and improves the spreading rate of water-based paints.

Uses:

- For interior and exterior use on old or new cement and gypsum surfaces.

Advantages:

- Excellent foundation for smooth and textures paint finishes .
- Excellent sealing properties .
- Very good adhesive strength .
- Moisture vapour permeable .
- Alkali resistant .
- Quick drying .
- Environmentally friendly .

Technical Characteristics: (at 25 ° C)

| | |
|-----------------------|---|
| Color: | White |
| Density: (Kg/L) | 1.3 ± 0.05 |
| Initial Drying Time: | 30 – 40 min. |
| Complete Drying Time: | 6 hours. |
| Dilution: | Diluted according to need with pure water. |
| Consumption Rate: | 10 – 12 m ² / L ≈ 8 – 10 m ² / kg . |

Application Method:

- Surfaces should be cleaned well free from dust, oils, grease and any contaminations.
- Apply HANZA SEAL with brush, roller or spray gun after stirring well before use.
- Apply one or more coats depending on the surface permeability.

Storage / Shelf life : One year under proper storing conditions.

Packs: 7.5 liter , 3 Kg .

