

Rolltone 50

ROLLTONE 50 is high quality matt latex paint in compliance with the Egyptian Standard Specifications No. 1539 of 2008 (internal work).

General Specifications:

- ROLLTONE 50 is bright weight matt emulsion paint, manufactured from vinyl acetate co-polymer resins, titanium dioxide and highly-smooth filling materials.

Uses:

- ROLLTONE 50 is used for new and old, cement and gypsum surfaces.

Technical Characteristics: (at 25 ° C):

Color:	White
Density:	1.6 ± 0.05 kg/L
Initial Drying Time:	20 - 30 minutes
Final Drying Time:	60 minutes
Dilution:	Diluted according to need with pure water
Consumption Rate:	9 - 11 m ² / L ≈ 6 -7 m ² / kg

How to Use:

- Surfaces should be cleaned well from dust, oils, grease or any other contaminations.
- Cavities should be filled and surfaces must be smoothed. One or more coats of HANZA SEAL Sealer diluted with water can be painted.
- Paint one or more coats of ROLLTONE 50 according to the surface permeability.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage: For two years under proper storing conditions.

Packs: 4 kg, 14 kg.