

Kematone Matt

KEMATONE MATT is a high quality latex paint for interior and exterior use.

Description:

- KEMATONE MATT is a bright white matt latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.
- KEMATONE MATT complies with Egyptian Standard Specifications 1539.

Uses:

- KEMATONE MATT is a matt paint for cement plastering, concrete, masonry, asbestos, wood and other surfaces.
- KEMATONE MATT can be applied on gypsum surfaces, after first applying a primer coat of ADDIBOND 65 diluted with water (ratio 1:3).

Technical Data: (at 25 ° C):

Color:	White & Colored
Density (kg/l.):	1.34 ± 0.02
Viscosity:	19.5 ± 1 poise
Consumption Rate:	6 – 8 m ² / kg / coat ≈ 8 – 10 m ² / liter

How to Use:

- Surfaces should be cleaned well from dust, oil, etc.
- Porous surfaces should be primed with a sealer coat of KEMABIND diluted with water (ratio 1:2). Cavities should be filled and surfaces must be smoothed using one or more coats of KEMATONE FINE PUTTY. Then apply an undercoat of KEMACOAT 400.
- Stir KEMATONE MATT well before use.
- Apply one or two coats of KEMATONE MATT according to surface condition using a brush, roller or spray gun.
- In case of spraying, dilute KEMATONE MATT with 5 - 10 % water for ease of application.

N.B. To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

Storage / Shelf life: 12 months under proper storing conditions.

Packs: 1 kg, 2.5 liter, 9 liter.