

## Kematone

KEMATONE is a high-quality semi-gloss latex paint for interior and exterior use.

### Description:

- It is a bright white semi-gloss latex paint, based on concentrated acrylic and vinyl acetate co-polymer emulsions, together with a high percentage of high quality titanium dioxide.
- Complies with Egyptian Standard Specifications 1539.

### Uses:

- Semi-gloss paint for cement plastering, concrete, masonry, asbestos, wood and other surfaces. It can be applied on gypsum surfaces, after first applying a primer coat of ADDIBOND 65 diluted with water (ratio 1:3).

### Technical Data: (at 25 ° C):

Color:	White & Colored ( Base A,B,C ) according to the required color
Density (kg/lit.):	1.26 ± 0.02
Viscosity:	14 ± 1 poise
Consumption Rate:	8 – 10 m <sup>2</sup> / kg / coat ≈ 10 – 12 m <sup>2</sup> / liter

### How to Use:

- Surfaces should be cleaned well from dust, oils, etc.
- Porous surfaces should be primed with a sealer coat of KEMABIND diluted with water (ratio 1:1) or Hanza seel.
- Cavities should be filled and surfaces must be smoothed using one or more coats of KEMATONE DELUXE PUTTY.
- Apply an undercoat of KEMACOAT 400 or ROLLTONE 50.
- Stir KEMATONE well before use.
- Apply one or more coats of KEMATONE according to surface condition using a brush, roller or spray gun. In case of spraying, dilute KEMATONE with 5 - 10 % water for ease of application.

**N.B.** To avoid color deviation from one batch to another, only use the same batch number in the same area, In the case of necessity to work with a different batch, apply one package and the color is checked before working with the rest of the quantity.

**Storage / Shelf life :** 12 months under proper storing conditions.

**Packs:** 1 kg , 2.5 liter, 9 liter.